

ENGINE DRIVEN WELDER MAGIC WELD 200 YD CHOPPER TECHNOLOGY

- Arc welding source in D.C. welding
- Welds any type of electrode, including cellulosic
- High frequency control of welding current and voltage
- MOSA Power Optimizer (patent pending)
- High performing alternator w/permanent magnets
- Single-Phase, 50Hz aux current, inverter generated
- Yanmar, air cooled, diesel engine
- Protective frame
- Wheels and handles (optional)
- Meets EC directives



Standard equipment 											
	<ul style="list-style-type: none"> • Remote control RC2 - RC2/90° (cable 20m) • Welding cables: K185 (4.5+3m, 35mm²) K190 (10+8m, 35mm²) K 200 (20+15m, 35mm²) 		<ul style="list-style-type: none"> • Welding parallel cables K 2x150 (35mm) 		<ul style="list-style-type: none"> • Manual trolley TRM-MW200 (n. 4 foldable handles) • Manual trolley CTM-MW200 						
	<ul style="list-style-type: none"> • Auxiliary output 230V a.c.: 1x230V 16A 2P+T CEE • Auxiliary output 230V a.c.: 1x230V 16A 2P+T schuko 				<ul style="list-style-type: none"> • Auxiliary output 110V 50Hz • Auxiliary output 110V 60Hz 						

Technical data

MAGIC WELD 200 YD

D.C. WELDING (Constant Current)

Current range, continuous	20 - 200 A
Duty cycle	170 A - 60%
Open circuit voltage	70 V

A.C. GENERATION - 50Hz

Permanent magnet alternator, self-excited, brushless

Single-phase generation (max)	3.3 kVA / 230 V / 14.3 A
Single-phase generation (continuous)	3 kVA / 230 V / 13 A
Insulation class	H

ENGINE

Gasoline, 4-stroke, OHV, air cooled

Model	Yanmar L70N
* Output	4.9 kW (6.7 HP)
Cylinders / Displacement	1/ 320 cm ³
Speed	3600 rpm
Fuel consumption (welding 60%)	1.0 l/h

* Maximum output (not overloadable) according to SAE J1349

GENERAL SPECIFICATIONS

Tank capacity	3.3 l
Running time (welding 60%)	3.3 h
IP protection degree	IP 23
* Dimensions LxIhx (mm)	630x490x540
* Dry weight	72 kg
** Acoustic power LwA (pressure LpA)	103 dB(A) (78 dB(A) @ 7 m)

* Values shown do not include trolleys

** For fixed installation only.

Maahantuoja:

ENDE-HITSI OY

Masalantie 357, 02430 Masala
Puh. 09-221 9370, Fax. 09-297 5859
www.endehitsi.fi

Mosa reserves the right to change this specification without notice. For further information please contact the sales department.